

Panda Bear 250H



APPLIED
adhesives
Equipment Solutions



Compact, Rugged, Simple, and Reliable

Your bulk unloader solution for one-component sealants and adhesives.



Features:

- Compact footprint
- All Pneumatic
- Heavy-Duty Chop check pump
- Double Acting for continuous pumping
- Adjustable flow rate
- Simplicity
- Rugged
- Air Inject to easy platen removal
- Pail stops and hold downs
- 1-3/4" Twin Post Rams
- Single tube platen seal
- Supply up to two applicators
- Power Ratio – 43:1
- 15 ft hose standard

Applications:

- Insulated Glass
- Glass Glazing
- Glass Embedding
- Transfer Pump
- Weather sealing
- Joint/Crack Filling/Sealing

Options:

- Flow control regulator
- Empty drum sensors
- Low-level sensor
- Stainless steel wetted components
- Boom Arm
- Casters
- Foot pedal start/stop
- 5 gal (20L) European Pails
- Ergonomic Dispensing Applicators
 - » 250H-01
 - » Ball Valve
 - » High-flow wand

Materials:

- Sealants
- Adhesives
- Polysulfides
- Silicones
- Epoxies
- Acrylics
- Urethanes
- Inks
- Mastics
- Lubricants
- Butyls
- PVC Sealers
- Caulking Compounds

Specifications:

- 5 gal (20L) Straight Wall Pails
- Weight: 150 lbs.
- Dimensions: 16"L x 24"W x 41"H
- Power Factor: 43:1
- Material inlet/outlet – 5/8" JIC
- Air Inlet – 1/4"
- Max Cycles Per Min: 60
- Max Flow Rate: Up to 0.75 gpm
- Viscosity Range 15,000 – 1,800,000 cps
- Fluid Pressure Range up to 3,000 psi
- Air Compressor Requirements: 4 CFM @ 90-110 psi

NORTH AMERICA BASED. CUSTOMER FOCUSED.

Since 1971, APPLIED Adhesives has been a trusted industry leader in custom adhesive solutions, offering a comprehensive portfolio of adhesive, equipment, parts, and services to meet your operational needs. Through our specialized brands we deliver advanced dispensing systems engineered for precision, reliability, and ease of use across industrial, construction, aerospace, and automotive markets.

Your custom adhesive solutions provider.



appliedadhesives.com



(800) 365-2480



6035 Baker Road
Minnetonka, MN 55345



info@appliedproducts.com